

**Reolink-Keen-IP-Camera-Specifications**

	<b>Model</b>	<b>Reolink Keen™</b>
<b>Hardware Features</b>	Image Sensor	1/2.7" CMOS Sensor
	Display Resolution	1920x1080 (2.0 Megapixels)
	Lens	f=4.0mm Fixed, F=2.0, with IR Cut
	Angle of View	Horizontal: 90° Vertical: 45°
	Pan/Tilt Angle	Horizontal: 355° Vertical: 105°
	Minimum Illumination	0 Lux (with IR Illuminator)
	IR Distance	12 Meters (40ft)
	Dimensions	103×95×117 mm
	Weight (Battery Included)	380g
	Interface	Built-in Micro SD Slot Built-in Microphone & Speaker Reset Button
<b>Software Features</b>	Protocols & Standards	SSL, TCP/IP, UDP, SMTP, DHCP, DNS, P2P
	Image Compression	H.264
	Maximal Frame Rate	15fps
	Code Rate	768Kbps ~ 2048Kbps
	Audio	Two-Way Audio
	Maximal User Access	Up to 8 Simultaneous Live Streams
	Browser Supported	Not Available
	Access to Camera	Smart Phone: iOS, Android Computer: Windows, Mac
	Standby Awaken	PIR Alarm, Remote Access, Reset Button
	Record Mode	PIR Alarm Record
<b>WiFi</b>	Wireless Standard	IEEE 802.11b/g/n
	Operating Frequency	2.4 GHz
	Wireless Security	WPA-PSK/WPA2-PSK
<b>Battery</b>	Battery Level Indication	Yes
	Ordinary Life	4 - 6 Months
	Endurance Ability	Daytime: 10 Hours, Night Vision: 5 Hours
<b>Other Parameters</b>	Temperature	Operating Temperature : -10°C~+55°C Storage Temperature: -40°C~70°C
	Humidity	Operating Humidity: 20% ~ 85% Storage Humidity: 10% ~ 90%
	Waterproof	NO
<b>PIR Sensor Hardware Features</b>	Detecting Distance	8M (26ft)
	Detecting Angle	Horizontal: 120°, Vertical: 60°
	Transmitting Frequency	433MHz (Wireless)
	Transmitting Distance	200M (Accessibility)
	Battery Life	3 Years
	Dimension	100x66.5x36.5 mm
	Weight (Battery Included)	65 g
	Temperature	Operating Temperature: -10°C~+55°C Storage Temperature: -40°C~70°C
	Humidity	Operating Humidity: 20%~85% Storage Humidity: 10%~90%
	Waterproof	NO